


ModuLED Nano Modular Passive Star LED Cooler ϕ 70mm

Features & Benefits

- For spot and downlight designs from 2,200 to 5,300 lumen
- Thermal resistance range R_{th} 1.8 - 2.2°C/W
- Modular design with mounting holes foreseen for a wide range of LED modules and COB's:
 - All Zhaga Book 3, Book 11 LED engines and holders
 - Bridgelux Gen7 Vero & Décor Vero 10/13/18, Vero SE & Décor Vero SE 10/13/18, Gen7 V 10/13/18/22, Vesta Tunable White 9/13mm & Dim-To-Warm 9/15mm
 - Citizen Cited CLU028/02J, CLU038/03J, CLU04J, CLU702, CLU712
 - Cree XLamp CXA13, CXB13, CXA15, CXB15, CXA18, CXB18, CMT14, CMT19, CMA13, CMA15, CMA18
 - Edison EdiPower II Star, Edison EdiPower III HM09/13/16/24/30
 - LG Innotek LEMWWM18 10W, 13W, 17W, 24W
 - Lumileds Gen4 Luxeon 1203, 1204, 1205, 1208
 - Luminus Gen4 CXM-4(Pico-COB)/6/9(AC/AA)/14(AC)/18, CIM-9/14/22, CLM-9/14/22, CGM-14, Gen3 CIM-9(AC)/14(AC), CLM-9(AC)/14(AC)/22(AC), CXM-9(AC)/11(AC)/14(AC)/18(AA), CHM-9(XD20), Dynamic CDM-9/14/18, CTM-14/18/22
 - Nichia NTCWT012B, NTCWS024B, NFCWL036-048-060-072B, NFCWD084-096B, NVNWS007Z, NJCWS024Z
 - Prolight Opto PACE, PACF
 - Seoul Semiconductor ZC6, ZC12, ZC18, ZC25, ZC40
 - Sharp Mega Zenigata, Tiger Zenigata, Mini Zenigata
 - Tridonic TALEXXmodule SLE GEN1 11/15mm, SLE GEN5 06/11/15mm, SLE GEN6 10/15/17mm
 - Xicato Chip on Board LED light source XOB09/14/23
- Diameter 70mm - Standard height 50mm & 80mm
Other heights on request
- Extruded from highly conductive aluminum



Zhaga
Book 3
Book 11

Order Information

LED Holders

**BENDER
+WIRTH**

BJB

IDEAL

TE
connectivity

LED Brands

bridgelux

CITIZEN
Micro HumanTech

CREE

EDISON

LG Innotek

Lit by
LUMILEDS

LUMINUS

NICHIA

OSRAM

LED Light for you
powered by OSRAM
CERTIFIED PARTNER

PHILIPS

ProLight Opto
Technology Corporation

SEUL
SEUL SEMICONDUCTOR

SHARP

TRIDONIC

VS LIGHTING SOLUTIONS

xicato

Example : ModuLED Nano 7050-B

ModuLED Nano 70 **1** - **2**

1 Height (mm)

2 Anodising Color
B - Black
C - Clear

ModuLED Nano is designed in this way that you can mount LED modules from various manufacturers on the same LED cooler
Simple mounting with self tapping screws
Recommended screw force 6lb/in
Screws are available from MechaTronix

ModuLED Nano Modular Passive Star LED Cooler $\phi 70\text{mm}$

Product Details

Model n°	ModuLED Nano 7050	ModuLED Nano 7080
Dimension (mm) ^{*1}	$\phi 70 \times h50$	$\phi 70 \times h80$
Volume (mm ³)	69498	112480
Cooling Surface (mm ²)	66919	104875
Weight (gr)	188	304
Thermal Resistance (°C/W) ^{*2}	2.2	1.8
Power Pd (W) ^{*3}	22.7	27.8
Heat Sink Material	AL6063-T5	AL6063-T5

^{*1} 3D files are available in ParaSolid, STP and IGS on request

^{*2} The thermal resistance Rth is determined with a calibrated heat source of 30mm x 30mm central placed on the heat sink, Tamb 40° and an open environment. Reference data @ heat sink to ambient temperature rise Ths-amb 50°C
The thermal resistance of a LED cooler is not a fix value and will vary with the applied dissipated power Pd

^{*3} Dissipated power Pd. Reference data @ heat sink to ambient temperature rise Ths-amb 50°C
The maximal dissipated power needs to be verified in function of required case temperature Tc or junction temperature Tj and related to the estimated ambient temperature where the light fixture will be placed
Please be aware the dissipated power Pd is not the same as the electrical power Pe of a LED module

To calculate the dissipated power please use the following formula: $Pd = Pe \times (1 - \eta_L)$

Pd - Dissipated power

Pe - Electrical power

η_L = Light efficiency of the LED module

Notes:

- MechaTronix reserves the right to change products or specifications without prior notice.
- Mentioned models are an extraction of full product range.
- For specific mechanical adaptations please contact MechaTronix.