




ZINC OXIDE VARI STOR 14Ø

Part No.	Maximum Allowable Voltage		Maximum Energy 10/1000 µs (J)	Withstanding Surge Current		Rated Wattage (W)	Varistor Voltage V1mA (V)	Maximum Clamping Voltage V50A (V)	  		
	ACrms (V)	DC (V)		1 time (A)	2 times (A)						
182KD14	1000	1465	336.0	4500	2500	0.6	1800 (1620-1980)	2970			
152KD14	750	1300	266.0				1500(1350-1650)	2475			
112KD14	680	895	217.0				1100 (990-1210)	1815	•		•
102KD14	625	825	217.0				1000 (900-1100)	1650	•	•	•
911KD14	550	745	217.0				910 (819-1001)	1500	•	•	•
821KD14	510	670	203.0				820 (738-902)	1355	•	•	•
781KD14	485	640	203.0				780 (702-858)	1290	•	•	•
751KD14	460	615	203.0				750 (675-825)	1240	•	•	•
681KD14	420	560	168.0				680 (612-748)	1120	•	•	•
621KD14	385	505	168.0				620 (558-682)	1025	•	•	•
561KD14	350	460	149.8				560 (504-616)	920	•	•	•
511KD14	320	415	149.8				510 (459-561)	845	•	•	•
471KD14	300	385	149.8				470 (423-517)	775	•	•	•
431KD14	275	350	145.6				430 (387-473)	710	•	•	•
391KD14	250	320	134.4				390 (351-429)	650	•	•	•
361KD14	230	300	123.2				360 (324-396)	595	•	•	•
331KD14	210	275	112.0				330 (297-363)	550	•	•	•
301KD14	190	250	103.2				300 (270-330)	505	•	•	•
271KD14	175	225	93.8				270 (243-297)	455	•	•	•
241KD14	150	200	82.6				240 (216-264)	395	•	•	•
221KD14	140	180	79.8				220 (198-242)	360	•	•	•
201KD14	130	170	79.8				200 (180-220)	330	•	•	•
181KD14	115	150	58.8				180 (162-198)	300	•	•	•
151KD14	95	125	51.8				150 (135-165)	250	•	•	•
121KD14	75	100	40.6				120 (108-132)	200	•	•	•
101KD14	60	85	33.6				100 (90-110)	165	•	•	•
820KD14	50	65	29.4				82 (74-90)	135	•	•	•
680KD14	40	56	23.8				68 (61-75)	*135	•	•	
560KD14	35	45	19.6				56 (50-62)	*110	•	•	
470KD14	30	38	16.8				47 (42-52)	*93	•	•	
390KD14	25	31	13.2	39 (35-43)	*77	•	•				
330KD14	20	26	12.3	33 (30-36)	*65	•	•				
270KD14	17	22	9.7	27 (24-30)	*53	•	•				
220KD14	14	18	7.6	22 (20-24)	*43	•	•				
180LD14	10	14	6.6	18 (15-21)	*38	•					
120MD14	7	9	4.2	12(9.6-14.4)	*25	•					

*680K-180L Max. Clamping Voltage testing current 10A.

STANDARD SERIES

Specifications are subject to change without notice, please contact our sales office before ordering.