

Talema Elektronik GmbH

Sembdnerstr.5, Postfach 2523, 82110, Germering.

Tel : ++49 89 841 00-0,


Fax : ++49 89 841 00 25

Email : info@talema.de



Customer	Schukat	Page : 1 of 1
Product	Current Compensated Choke	
Part No	21413	Date : 16th Feb '10
Customer Part No	Equiv. to 42V30 10 00	


SCHEMATIC:




ELECTRICAL SPECIFICATIONS @25°C:

- 1) Lo / Wdg = 27.00 mH +50%, -30% @10KHz/0.1mA
- 2) DCR / Wdg = 600 mOhms (Typ)
- 3) Turns Ratio W1 : W2 = 1 : 1
- 4) H.V. Test:
Wdg - Wdg = 1.5KVrms / 50Hz / 2sec
- 5) Voltage = 250Vac
- 6) Rated current = 1.0A - referred to 250V-50Hz
- and +60° ambient temperature
- 7) Climatic category = DIN GKC (-40° to +125°C; Humidity cat. C)

MECHANICAL SPECIFICATIONS:




Front View




Side View

Case accordance with UL94-V0



Pin View

Impedance Curve



Unit : mm

Pin pitch tolerance : ±0.2mm



Rev.	Description	Date	Name
3			
2			
1			
0	Initial issue	16.02.2010	K.Veerappan

DRAFT COPY

ISSUE : 1

REV : 0