

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT 19

ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
AP	-	P	LTR	DESCRIPTION	DATE	DWN	APVD
			C	REVISED BY ECO-07-018018	04SEP2007	RKTL	LWP
			D	CHANGED STATUS ECO-11-009754	22JUN2011	MAS	MG

SECTION A-A

① - ELASTÔMERO SAE J200, 2BC 414, A14, B14, C12, E014, F17, Z1  
Z1=RESISTÊNCIA RASGO, ASTM D624 - 20kg/cm MIN.

② - ELASTÔMERO SAE J200, 2BC 514, A14, B14, C12, E014, F17, Z1  
Z1=RESISTÊNCIA RASGO, ASTM D624 - 20kg/cm MIN.

③ - ELASTOMERO SAE J 200M, 2GE, 405, A19, B37, EA14, E016, E036, F19, G11, Z1 Z1 = EXTERNAMENTE LUBRIFICADO 2%

① - ELASTOMER SAE J200, 2BC 414, A14, B14, C12, E014, F17, Z1  
Z1= TEAR RESISTANCE, ASTM D624 -20kg/cm MIN.

② - ELASTOMER SAE J200, 2BC 514, A14, B14, C12, E014, F17, Z1  
Z1= TEAR RESISTANCE, ASTM D624 -20kg/cm MIN.

③ - ELASTOMER SAE J 200M, 2GE, 405, A19, B37, EA14, E016, E036, F19, G11, Z1 Z1 = 2% LUBRIFICATED EXTERNALY

③	PRETO/BLACK	40±5 SHORE A	SILICON ③	880811-3
	PRETO/BLACK	40±5 SHORE A	ELASTOMER ①	880811-2
②	PRETO/BLACK	50±5 SHORE A	ELASTOMER ②	880811-1
	FINISH	HARDNESS	MATERIAL	PART NUMBER

DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD		NAME	
mm		0 PLC	±-	J.M.M. NETO		COVER CAP 3 POSN	
		1 PLC	±0,3	PRODUCT SPEC		-	
		2 PLC	±-	APPLICATION SPEC		-	
		3 PLC	±-	WEIGHT		-	
		4 PLC	±-	CUSTOMER DRAWING		SCALE 2:1	
		ANGLES	±1°			SHEET 1 OF 1	
MATERIAL SEE TABLE		FINISH SEE TABLE		SIZE A3		CAGE CODE 00779	
				DRAWING NO C-880811		RESTRICTED TO -	
						REV D	

**DO NOT REVISE EXCEPT BY CAD**

1470-19 (3/11)