3900 Metal Toggle Switches 16A 250Vac - IP67 Sealed Versions





Key Features

- Metal toggle switches
- Ratings up to 20A, 277V ac
- Single and double pole
- O Choice of circuits including 3 position and momentary
- Sealed version supplied complete with gaskets
- O Panel seal version to IP67
- 0 6.3mm terminals
- O Guard option

Terminal	Function		Actuator	Body	Options
C 10.5	Single Pole 3900 ON - OFF	Double Pole 3950 ON - OFF	Metal Metal toggle finish is nicikel plate	Single pole Thread: 15/32* x 32TPI Keyway 17,5 10,5 17,0	Neck Seal M539 Actuator is visible Cover M1080
S	3901 ON - OFF (momentary ON) 1 3902 ON - OFF (momentary OFF)	3951 ON - OFF (momentary ON) 1 3952 ON - OFF (momentary OFF)	B 17.5 Metal Metal loggle finish is nickel plate	Panel sealed, single pole Thread: 15/32" x 32TPI Keyway Panel Reyway Double pole, without barrier	Covers have internal nylon nuts M1080-2
Screw & Clamp	3910 ON - ON 3911 ON - ON (momentary 1 side)	3960 ON - ON 3961 ON - ON (momentary 1 side)	25.4	Thread: 15/32* x 32TPI 60x39 17.5 10.0 30.6 B Double pole, with barrier	Covers have internal metal hex nuts Fixing nuts Nickel plated brass are supplied
T 10.5	3920 ON - OFF - ON μ 3921 ON - OFF - ON μ (momentary 1 side) 3922 ON - OFF - ON μ (momentary 2 sides)	3970 ON - OFF - ON μ (momentary 1 side) 1:1:1: 3972 ON - OFF - ON μ (momentary 2 sides)	E 38.1	Thread: 15/32' x 32TPl Keyway Panel sealed, double pole, with terminal barrier Thread: 15/32' x 32TPl Keyway Thread: 15/32' x 32TPl Keyway Switches with F toggles have double pole bodies, regardless of circuit	Knurled Front nut Panel thickness 4.0 with backnut Plate P236 Plate SP or DP
			rickel plate	Panel sealed, double pole, without terminal barrier Thread: 15/32" x 32TPI Keyway Feel 17-5 1070 31*1	



Approvals and specifications

W UL/CSA Ratings 3901, 3902, 3920, 3921, 3922 16A, 277Vac 1 HP, 250Vac

91 © 7A, 72Vdc 14A, 36Vdc

> 3910, 3901, 3952, 3960, 3961, 3970, 3971, 3972 16A, 277Vac 1 HP, 250Vac 1/2 HP, 125Vac 7A, 72Vdc 14A, 36Vdc

3900, 3950 20A, 277Vac 1 HP, 250Vac 1/2 HP, 125Vac 7A, 72Vdc 14A, 36Vdc

ENEC Ratings 3900, 3901, 3902, 3950, 3952, 3960, 3961 16(4)A 250Vac

3910, 3911, 3920, 3921, 3922, 3951, 3970, 3972 10 4)A 250Vac

Approvals and ratings vary with function. 3mm contact gap except where marked $\boldsymbol{\mu}.$

* CSA approval for A and B bodies only

Dimensions mm) * Indicates ON position (for ON - OFF switches)

Single pole


(C terminals shown)

























Toggle Switch - sealed version

BE and BF types







Examples







C3920BA - - -



C3950BF - - -



☑ C3972BB - - -





Key Features

- Nylon toggle switches
- Ratings up to 20A, 250V ac
- Single and double pole
- Wide choice of terminals
- Choice of circuit options including 3 position
- Flat & round actuator options

Approvals and specifications

4 16(4)A 250Vac T85

UL 20A 250Vac Non Ind (Single pole)
UL 16A 250Vac Non Ind (Double pole)
UL CSA (2 pos types) 250Vac 1hp, 125Vac 1/2hp
UL CSA (3 pos types) 250Vac 1/2hp, 125Vac 1/4hp
CSA 16A 250Vac Non Ind
UL 85°C, file E45221, CSA file LR10990
UL and CSA N/A on momentary types

Selective "A, B, C" and "OFF, A, A+B" circuits at 5 amp also available. 3mm contact gap except where marked μ .

Terminal	Function	Actuator	Body	Options
C 9.1	Single Pole Double Pole 1700 ON - OFF ON - OFF	H 16.4	O Single pole Thread: 15/32" x 32TPI	Neck Seal M539 Material - Nitrile (H & R Actuators) Actuator visible Cover M1080 Material - EPDM (R Actuator only)
K 2.0 19.1	1710 μ 1760 μ ον-ον 1770 μ ον-ορε-ον ον-ορε-ον	R	Double Pole Thread: 15/32* x 92TPI Keyway 10.0 11.1	Cover M531 Material - PVC (R Actuator only) Covers have internal nylon nuts Fixing nuts (Standard is M506 & T92)
X 4.0 \$\frac{1}{2},0	1721 μ ON - OFF - ON μ (momentary 1 side)	The switch is on	Panel hole (all types) Panel thickness (Max) Both nuts - 3.5mm Less backnut - 6.5mm	T5 Hex brass M506 Hex nylon 15,2
	1722 ON - OFF - ON µ (momentary 2 sides)	between centre terminals (2 & 5) and the terminals over which the lever is positioned.		Plate P236 Plate SP or DP



Dimensions mm) * Indicates ON position (for ON - OFF switches)

Single pole

(C terminals shown)







Optional F00232PAAA plate SP or DP

Double pole

(C terminals shown)





With barrier

Without barrier

1A 2A 3A

Examples









C1700R - -C1700H - -

C1760R - -

C1750H - -